SOLTEC

BORDO

LVT dryback

Essential data

0,55
mm
wear layer

2,50
mm
total thickness

6
dB
acoustical insulation

V4
bevels

4500 **gr**
weight pro sqm

Bfl-S1
reaction to fire

23|33|42
classification

EIR

Find out all about our collection on the product page!

SOLTEC Premium

Colours and designs

Bordo: Crafted for the modern home. Eleven remarkable décors with synchronized relief for a woodlook that feels as real as it lives.

** These decors are also available in our click-collection SOLTEC.*

SOLTEC Premium

Our commitments

15 5
along conditions

INDOOR AIR QUALITY*
A+
A+ A B C

SANS PHTHALATES FREE

25% recycled materials,
100% recyclable
using 30% renewable energy in production

SOLTEC Premium

Contact us

Benoît DERAEDT
Chief Executive Officer &
Sales Europe & global
0032 493 52 98 58
benoit@soltec.be

Laura SLOS
Internal sales
0032 56 92 19 90
laura@soltec.be

Nele VERKEST
Finance & Administration Manager
0032 56 92 19 91
nele@soltec.be

GENERAL CONTACT DETAILS
Kortrijkstraat 19/0001
B-8580 Avelgem
BELGIUM

Thanks to our expertise in sourcing, logistics, and modern stock management – and with a central warehouse of over 250,000 m² in Belgium – we're always ready to serve customers across Europe and worldwide with unmatched speed.

Technical data sheet

Specification	Norm	Value
Classification	EN ISO 10874	23 | 33 | 42
Dimensions	EN ISO 24342	18,70 x 122,70 cm
Box content		18 planks
Surface pro box		4,13 sqm
Total thickness	EN ISO 24346	2,50 mm
Thickness of wear layer	EN ISO 24340	0,55 mm
Total weight	EN ISO 23997	4500 gr/sqm
Surface protection		Aluminium Oxide Coating
Embossing		EIR
Bevelled edges		V4
Installation method		Gluedown
Dimensional stability	EN ISO 23999	≤ 0,17 %
Residual indentation	EN ISO 24341-1	≤ 0,10 mm
Acoustical impact noise reduction	EN ISO 717-2	6 dB
Light stability	EN ISO 105-B02	6 - 7
Resistance to household chemicals		OK
Slipresistance	EN 13893 DIN 51130	> 0,30 R10
Underfloor heating suitable	EN ISO 12524	OK max 30 °C
Reaction to fire	EN ISO 13501-1	Bfl-S1
Use of solar energy		30 %
Re-use of water		30 %

Check out the full technical specifications!

SOLTEC Premium