



SOLTEC

INVERNO

Rigid core SPC with integrated acoustical underlay

Essential data

0,30

mm
wear
layer

1,00

mm
integrated
underlayer

4,50

mm
total
thickness



angle- tap

19

dB
acoustical
insulation

7468 gr

weight pro sqm

Bfl-S1

reaction
to fire

23|31

classification

V4

bevels



structured

Colours and designs

”

*A short and striking click collection with a wear layer of 0.30 mm
– perfectly suited to market demand.*



Our commitments



*25% recycled materials,
100% recyclable
using 30% renewable energy in production*

Contact us



Benoît DERAEDT

Chief Executive Officer &
Sales Europe & global
0032 493 52 98 58
benoit@soltec.be

Gilles DECOUVER

Internal sales
0032 56 92 19 92
gilles@soltec.be



Nele VERKEST

Finance & Administration Manager
0032 56 92 19 91
nele@soltec.be

GENERAL CONTACT DETAILS

Kortrijkstraat 19/0001
B-8580 Avelgem
BELGIUM



”

Thanks to our expertise in sourcing, logistics, and modern stock management – and with a central warehouse of over 250,000 m² in Belgium – we're always ready to serve customers across Europe and worldwide with unmatched speed.

Technical data sheet

Specification	Norm	Value
Classification	EN ISO 10874	23 31
Dimensions	EN ISO 24342	18,00 x 122,00 cm
Box content		10 planks
Surface pro box		2,20 sqm
Total thickness	EN ISO 24346	4,50 mm (3,5 mm SPC + 1 mm IXPE)
Thickness of wear layer	EN ISO 24340	0,30 mm
Total weight	EN ISO 23997	7468 gr/sqm
Surface protection		Polyurethane (PU)
Embossing		Structured
Bevelled edges		V4
Installation method		Unilin angle-tap
Dimensional stability	EN ISO 23999	≤ 0,08 %
Residual indentation	EN ISO 24341-1	≤ 0,10 mm
Acoustical impact noise reduction	EN ISO 717-2	19 dB
Light stability	EN ISO 105-B02	≥ 6
Resistance to household chemicals		OK
Slipresistance	EN 13893 DIN 51130	D5 R9
Underfloor heating suitable	EN ISO 12524	OK max 30 °C
Reaction to fire	EN ISO 13501-1	Bfl-S1
Use of solar energy		30 %
Re-use of water		30 %